

# 3" Forward Control Extension Kit

Part# 07-610 Fits: 2000-2006 Softail Models



Thank you for purchasing this Arlen Ness product. We believe that our products are the very best available and are engineered to provide a lifetime of use. Our forward control extension kit is ideal for taller riders who want a more comfortable ride by allowing three inches of forward stretch. Designed to work with OEM foot controls. **NOTE:** Basic hand tools and an OEM service manual for your year and model motorcycle are all that is necessary to complete this installation.

## Parts Included:

1- 07-610-1B, Adapter plate, right	1- 07-610-5, Rear brake line	2- H-011 Cable ties
1- 07-610-2B, Adapter plate, left	1- 07-610-3R, Retaining pin	1- 07-610-4P, Shift rod
1- 07-610-6B, Brake tee bracket	1- 07-610-7, Brake switch ext harness	1- 07610-I, Instruction sheet
6- H-534Z, 3/8-16 x 1" countersunk allens, zinc	2- H-839S, 1/4-20 x 1/2" button head cap screws, ss	

Supplies Needed: #242 blue thread locker and appropriate service manual for your motorcycle

1. Begin the installation by removing the kickstand, shift rod and foot shift assembly from your motorcycle as outlined in the procedure listed in your service manual. Keep all hardware removed from your motorcycle handy as it will be used to reinstall the foot shifter assembly in the next step. If the threads on any of the OEM bolts are dirty, clean with a wire brush or wire wheel.
2. Relocation of the shift side foot control requires a new location for the kickstand return spring. Press the retaining pin included with this kit into the left hand extension plate prior to installing the plate to the motorcycle. Now install the left hand extension plate (each plate is marked "LEFT" or "RIGHT") to the motorcycle using the flat head cap screws provided in this kit. Use thread locker and torque them to the specifications listed in your service manual. Now, using thread locker on the bolts, reinstall the OEM foot shifter assembly and kickstand using the original hardware. Thread in the extended shift rod and adjust it to provide the desired position of the foot shifter.
3. Remove the rear brake line as well as the rear brake control as outlined in your service manual. Again, keep all hardware removed from your motorcycle handy as it will be used to reinstall the rear brake control in the next step. If the threads on any of the OEM bolts or screws are dirty, clean them with a wire brush or wire wheel.
4. Install the right hand extension plate to the motorcycle using the flat head cap screws provided in this kit. Use thread locker and torque them to the specifications listed in your service manual. Now, using thread locker on the bolts, reinstall the OEM rear brake control using the original hardware. Replace the OEM rear brake line with the extended line supplied in this kit and bleed the rear brake as outlined in your service manual. For 2004 and up Softail models, a black mounting bracket is supplied to allow the included "T" fitting to be mounted to the frame using the existing hole in the frame rail near the exhaust bracket bolt holes.

**Maintenance Tip:** To keep the chrome and polished stainless steel hardware used in your new forward control extension kit looking it's best, we recommend applying a high-quality chrome polish to them every time you detail your motorcycle. Also, check all connections and fasteners as part of your regular maintenance routine.