

CIRO ACCESSORY PERCH MOUNT

PARTS INCLUDED

- 1 Perch Mount
- 1 Installation Kit
 - 2 1/4-20 SHCS
 - 2 M6 SHCS
 - 2 Spacers
- 1. Park on a level surface and shut off the motorcycle. Ensure that the engine has time to cool before installation. Cover your tank with a clean towel or blanket to protect it.
- 2. Determine which side of the handlebars you would like the mount. Remove the two screws holding the clamp half in place. Carefully support the original clamp half and controls to prevent any accidental damage. (Fig. 1)









- 3. Compare the screws you removed to the screws included in this kit. Both 1/4-20 and M6x1.00 threaded screws are included to cover a variety of applications. Use the screws that match your motorcycle. Prepare the perch mount as shown above. (Fig. 2)
- 4. Install the perch mount with spacers to the motorcycle, making sure to re-use the original clamp half. Tighten to factory specifications; approximately 72-108 in-lbs (8.1-12.2 Nm). (Fig. 3)
- 5. The position of the top ball can be adjusted to provide adequate clearance for any installed accessory. Use a 5/32" hex key to loosen and adjust the position, checking final tightness before riding. (Fig.4)
- *If you have purchased any Ciro accessories to go with your ball mount, please refer to those instructions to complete your installation.

WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro® warrants that products sold hereunder to the original purchaser, if maintained and operated under normal conditions, shall be free from any defects in materials and workmanship for a period of (3) years from date of purchase, and a lifetime warranty against LED failure.

Ciro will have no obligation if the customer cannot show proof of purchase.

Warranty will not be granted unless the part is properly installed and maintained.

Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website Ciro3d.com for our complete warranty policy.





SMARTPHONE HOLDER


Parts Included:

- l Smartphone Holder Assembly
- l Wiring Harness (Powered Model Only)

Installation Instructions:

1. Remove the large plastic nut from your smartphone holder and slide it over the Ciro ball mount with the threads facing outward.





- 2. Snap your smartphone holder onto the ball and thread the large plastic nut onto the drink holder. Adjust the angle and tighten it down.
- 3. Flip up the side lever on the smartphone holder and adjust it to the size of your phone. Your device should have just enough space to slide in and out. When adjusted correctly, flip the lever down to secure your device.
 *Note: The lever can be put on either side if unscrewed all the way.

Powered Model Only

4: Connect the included wiring harness to your battery and route the wires to where you have mounted the smartphone holder. Plug the power jack into the phone holder and then your USB cable into the holder and device.

*Note: USB cable not included

WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure. Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed and maintained. Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products. Please visit our website Ciro3d.com for our complete warranty policy.

CIRO.3D.COM