

| Items Supplied > | Application(s) > |
|---|--|
| 1 - Sissy Bar w/pad 2 - Brackets 4 - 8mm x 16mm Button head Bolts 4 - 8mm x 40mm Button head Bolts | Yamaha V-Star 650 Classic 98-10 |
| Instruction Manual > | 02-4701/02-5201/02-5701 |
| Your sissy bar will install in just a few minutes usin completely before installing your new sissy bar. | ng common tools. Read all instructions carefully and |
| 1. Remove the two (2) rear bolts on each fender ra | ail. |
| 2. Install the brackets with the bent portion toward tighten. Brackets will mount on the outside of fer | the inside (part number) using supplied 8mm x 40mm bolts and nder rail. |
| 3. Install the sissy bar to the brackets using the su | upplied 8mm x 16mm bolts and tighten. |
| | nile riding. Please never operate your motorcycle while under new look of your motorcycle and please ride safely. Anything's Possible. _® |
| | |
| COBRA ® 23801 E. La | Palma Ave., Yorba Linda, Ca 92887 Ph. 714.692.8180 Fax. 714.692.5016 |

| Items Sunnlied > | Application(s) > | www.cobrausa.com |
|---|---------------------------------|------------------|
| 1 - Sissy Bar w/pad 2 - Brackets 4 - 8mm x 16mm Button head Bolts 4 - 8mm x 40mm Button head Bolts | Yamaha V-Star 650 Classic 98-10 |) |
| | | |

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

- 1. Remove the two (2) rear bolts on each fender rail.
- 2. Install the brackets with the bent portion toward the inside (part number) using supplied 8mm x 40mm bolts and tighten. Brackets will mount on the outside of fender rail.
- 3. Install the sissy bar to the brackets using the supplied 8mm x 16mm bolts and tighten.
- * Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

Instruction Manual S

02-4701/02-5201/02-5701