

## Slick Signal L/P (Curved) with LED's

(Part # CV4650) Chrome- (Part # CV4650B) Black Fits 2013-2017 FXDB (Part # CV4651) Chrome-(Part # CV4651B) Black Fits 2010-2015 FXDWG

Parts Included: 1ea-CV4650 bracket 1ea-CV4621/B Slick Signal L/P (Curved) w/LED's 1ea-CV4813B Turn Signal Recess Cover-BLACK

## NOTE: AFTER INSTALLATION SOME 2016 AND NEWER MODELS WILL HAVE A RAPID FLASH OF THE TURN SIGNALS.IN THIS CASE THE CYCLE VISIONS PIGTAIL ADAPTER (CV4715) AND THE KURYAKYN LOAD EQUALIZER (pn 5498). (BOTH ITEMS SOLD SEPARATELY) WILL BE REQUIRED TO REGAIN NORMAL TURN SIGNAL FUNCTION.

- 1. Must be installed by a Qualified Technician
- 2. Remove seat and locate and remove the tail light and turn signal harness adapter from the 8 pin plug as shown in figure 1.
- 3. Remove both rear turn signals from the bike.
- 4. Lower the gold turn signal support bracket located inside of rear fender.
- 5. Install the nut-serts thru the CV4650 bracket as shown in figure 2 and 2-A.
- 6. Raise and align the turn signal support bracket with holes in the fender and strut.
- 7. Install the CV4813 Turn Signal Recess Cover as shown in fig 3.
- 8. Remove nuts from the License plate cover and two of the set screws.
- 9. Remove the License Plate frame from the bracket.
- 10. Notch the License Plate to clear the wire harness as shown in fig 4.
- 11. Reinstall the License Plate frame.
- 12. NOTE: USE ALLEN WRENCH TO HOLD SETSCREW WHILE TIGHTENING LOCK NUT
- 13. Do not over tighten setscrews.
- 14. Use locktite when installing screws.
- 15. We will not warranty the license plate frame if the setscrew goes through face of the frame.
- 16. Route the wire harness thru the wire loom along the right side of the fender and thru the hole in the fender.
- 17. Install the plug into the 8 pin stock connecter.
- 18. Check for proper operation.
- 19. Re-install seat.

## Our Warranty Policy

Cycle Visions' obligation under "Our Warranty Policy" is limited to one (1) year from date of purchase to repair or replacement of the defective item (s). Chrome, polished, powder-coated, anodized finishes, or electrical parts are limited to thirty (30) day from date of purchase.

This warranty will be void on all products that show evidence of misapplication, improper installation, abuse, lack of proper maintenance, negligence, or alteration from their original design.

The consumer will be responsible for removing from the vehicle any defective item (s), transportation costs prepaid and for reinstallation upon return by Cycle Visions. The loss of use of the product, loss of time, inconvenience, commercial loss or consequential damages is not covered. Cycle Visions reserves the right to change the design of any product submining any obligation to modify any product previously manufactured. Warranty returns of Cycle Visions products are few because of our high quality products.

Carefully inspect all parts.... If you find that your parts arrived in damaged conditional all original packaging material (box and other materials) must be saved to make a proper damage claim within seven (7) days. You must be able to present the damaged boxes and materials to the freight carrier to verify your claim. The user shall assume all legal, personal, injury risk and liability and all other obligations, duties and risks associated therewith.

Cycle Visions

San Diego, CA (619) 295-7800 See our other products on the web!

www.cyclevisions.com



Fig 1



Fig 2



Fig 2-A



Fig 3



