



## TWO-PIECE FORK MOUNT

## 2275

### 54-58MM FORKS

**FITS: UNIVERSAL FOR 54-58MM DIAMETER FORKS, HONDA, KAWASAKI, SUZUKI, YAMAHA**

#### PARTS INCLUDED

- 2 Outer Clamps
- 2 Inner Clamps
- 1 Hardware Kit Including:
  - 2 5/16-18 x 3/4" Button Socket Cap Screw (BSCS)
  - 4 10-24 x 3/8" Socket Head Cap Screw (SHCS)
  - 2 5/16" Tooth Washer
  - 2 Thin Reducer Rings
  - 2 Thick Reducer Rings
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

#### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

#### TOOLS SUGGESTED

Set of hex wrenches.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

#### PROCEDURE

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

**STEP 2** Determine a mounting location in either the forward or the rear position as shown in PIC. 1.

**-cont.-**



#### CUSTOMER SERVICE

877.370.3604 (toll free)

#### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

#### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in non-conforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

#### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



**STEP 3** Secure the light (not included) to the outer clamp half as shown in PIC. 2, we have included a 5/16-18 x 3/4" BSCS screw in the hardware kit or use the hardware from the light kit.

**NOTE:** May use the included star washer between the clamp half and the light to prevent the light from rotating.

**STEP 4** Hold the clamp up to the fork, and adjust the position of the light to the desired orientation; tighten the fastener that secures the light to the outer clamp half.

**STEP 5** Refer to Chart 1 to determine which (or, if) a spacer is needed. 54mm forks will use the larger spacer, 56mm forks will use the smaller spacer and 58mm forks will not use a spacer.



PIC. 2

CHART 1

CRUISER MODEL	CLAMP SIZE
<b>HONDA</b>	
VTX1800C/F/R/S/T without Chrome Forks	56mm
<b>KAWASAKI</b>	
Mean Streak 1600	54mm
<b>SUZUKI</b>	
M50	55mm
M109	58mm
<b>YAMAHA</b>	
Road Star Warrior	54mm
<b>VICTORY</b>	
Hammer	56mm
Kingpin	56mm

**STEP 6**

If using a spacer, lightly pull the halves apart and place on the fork, positioning it in the location where the clamp will be located.

**ATTENTION!** Determine the mounting location and orientation of the clamps before fully tightening the screws. The clamp may leave marks when tightened down.

**STEP 7**

Place the inner and outer halves of the clamp over the spacer (fork) and insert two 10-24 x 3/8" SHCS screws to attach the two halves together.

**NOTE:** It may be helpful to rotate the clamp halves to start the screws, and then rotate the clamp and finish tightening the screws.

**STEP 8** Repeat STEP 2 through STEP 7 for the other side.

**STEP 9** Turn the handlebars in both directions to their full stop position to make sure that there is clearance for the lights.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*