

INSTALLATION INSTRUCTIONS

HEEL SHIFT LEVER FOR INDIAN® , GLOSS BLACK

5648

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- | | | | |
|---|--------------------|---|--------------------------------|
| 1 | Heel Shifter Lever | 1 | Hardware Kit, containing: |
| | | 2 | M6 X 1.0 X 20MM Screws |
| | | 2 | 1/4 Type B Narrow Flat Washers |

YOU WILL ALSO NEED:

Hex wrench set, combo wrench set

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2** Refer to PIC 1. Disconnect the front bolt connecting the shifter linkage to the bike. Leave the back end of the shifter linkage attached to the bike. Set hardware aside until later.
- STEP 3** Refer to PIC 1. Disconnect floorboard mounting bracket and remove floorboard and shifter lever as a unit. Set hardware aside until later.
- STEP 4** Refer to PIC 2. Locate provided Heel Shifter Lever, two (2) M6 X 1.0 X 20MM Screws, and two (2) Flat Washers. Place a washer on each screw.
- STEP 5** Refer to PIC 3. Align the holes of the Heel Shifter Lever with the holes of the toe shifter lever. The Heel Shifter Lever should be placed on the inside, closest to the floorboard.



INSTALLATION INSTRUCTIONS

HEEL SHIFTER LEVER FOR INDIAN®, GLOSS BLACK

5648

-CONTINUED-

- STEP 6** Refer to PIC 4. With the washer placed on a 20MM screw, insert the assembly into the top holes on the back side of the aligned levers; loosely tighten. Adjust the Heel Shifter Lever's bottom hole to be seated towards the back of the oblong hole of the toe shifter. Insert the screw and washer assembly into bottom hole. Fully tighten both screws.

Note: It is important that the bottom hole of the Heel Shifter Lever is positioned correctly, otherwise you may encounter clearance issues between the floorboard and Heel Shifter Lever.

- STEP 7** Attach Shifter Peg (sold separately) to Heel Shifter Lever.

- STEP 8** Refer to PIC 5. Loosen the two nuts and adjusters on each end of the shifter linkage.

Note: Each side is threaded differently. One is left thread and the other is right thread. This is important to know when you re-tighten them later.

- STEP 10** Refer to PIC 6. With the shifter linkage positioned below the mounting bracket, align and fasten the assembly to the bike using the bolts that were removed in Step 3. Fully tighten hardware.

- STEP 11** Refer to PIC 6 and 7. Reconnect the shifter linkage to the bike. Adjust the position of the heel and toe shifter levers up and down by twisting the shifter linkage bar. Once levers are in desired position, fully tighten the lock nuts on each end.

- STEP 12** Verify that you have clearance on all moving parts and that nothing is binding.

CAUTION ENSURE THAT THE INSTALLATION OF THIS PRODUCT DOES NOT INTERFERE WITH THE PROPER OPERATION OF THE MOTORCYCLE BEFORE RIDING.

NOTICE IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



INSTALLATION INSTRUCTIONS

HEEL SHIFT LEVER FOR INDIAN® , GLOSS BLACK

5648

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice