

INSTALLATION INSTRUCTIONS

DRIVER FLOORBOARD SPACERS FOR FL SOFTAIL, GLOSS BLACK

7508

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- | | | | |
|---|--------------------|---|--------------------------------------|
| 1 | Left Front Spacer | 1 | Hardware kit, containing: |
| 1 | Left Rear Spacer | 4 | 3/8-16 X 2.5" Socket Head Cap Screws |
| 1 | Right Front Spacer | | |
| 1 | Right Rear Spacer | | |

YOU WILL ALSO NEED:

Torx wrench set, hex bit set, ft-lbs (Nm) torque wrench

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

*Note: Take note of the stampings made on the back side of the spacers.
LF = Left Front and LR = Left Rear (clutch side)
RF = Right Front and RR = Right Rear (brake side)*

STEP 2 Refer to PIC 2 and 3. On the right (brake) side, unfasten the existing driver floorboard mounts and remove the whole assembly. Set floorboard and mount assembly aside, they will be reused.

STEP 3 Refer to PIC 4 and 5. Locate provided Right Rear Spacer, Right Front Spacer, two (2) screws, and the existing driver floorboard assembly. On the inside edge of the floorboard mount align and place the rear spacer on the rear mount leg and the front spacer on the front mount leg. The letter stampings on the spacers should be readable from on top of the mount legs.



KURYAKYN.COM

INSTALLATION INSTRUCTIONS

DRIVER FLOORBOARD SPACERS FOR FL SOFTAIL, GLOSS BLACK

7508

-CONTINUED-

STEP 4 From the outside edge of the floorboard mount, insert a screw through each of the mounting holes and spacers to keep them in place.

STEP 5 Refer to PIC 6. Align the driver floorboard mount, with the screws and spacers attached, with the mounting holes on the bikes. Insert and fasten the screws to the bike frame. Fully tighten hardware.

STEP 6 Refer to PIC 7. On the left (clutch) side, unfasten the existing driver floorboard mounts and remove the whole assembly. Set floorboard and mount assembly aside, they will be reused.

Note: For ease of installation unfasten the shift lever from the floorboard assembly. If you leave it attached you will need to hold the assembly up during the installation process.

STEP 7 Locate provided Left Rear Spacer, Left Front Spacer, two (2) screws, and the existing driver floorboard assembly. On the inside edge of the floorboard mount align and place the rear spacer on the rear mount leg and the front spacer on the front mount leg. The letter stampings on the spacers should be readable from on top of the mount legs. The boss located on the Left Rear Spacer should align with the bike frame mounts.

STEP 8 From the outside edge of the floorboard mount, insert a screw through each of the mounting holes to hold the spacers in place.

STEP 9 Refer to PIC 8 and 9. Align the driver floorboard mount, with the screws and spacers attached, with the mounting holes on the bikes. Insert and fasten the screws to the bike frame. Fully tighten hardware.

STEP 10 Fully tighten all hardware and both sides.

TORQUE VALUE FOR FLOORBOARD MOUNT SCREWS:
40-45 FT-LBS (54.2-61NM)

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



PIC 6



PIC 7



PIC 8



PIC 9



FINAL



INSTALLATION INSTRUCTIONS

DRIVER FLOORBOARD SPACERS FOR FL SOFTAIL, GLOSS BLACK

7508

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

