



# INSTALLATION

## FLUSH MOUNT NON-VENTED GAS CAP 8310

### PARTS INCLUDED

- 1 Inner and Outer Non-vented Gas Cap
- 2 Brass Installation Pins
- 1 Beveled Gasket
- 1 OEM Style Gasket
- 1 Key
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

### TOOLS SUGGESTED

Six Inch Screwdriver, Set of Hex Wrenches, Set of Combination Wrenches

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

**WARNING!** YOU WILL BE WORKING AROUND AN OPEN FUEL TANK AND GAS FUMES. SPARKS OR AN OPEN FLAME MAY IGNITE THE FUMES AND CAUSE SERIOUS INJURY OR DEATH.

**CAUTION!** Care must be used when the gas cap is removed so no foreign objects fall into the fuel tank.

**STEP 2** Remove the stock gas cap. Thoroughly clean the surface around the tank opening (bung).

-cont.-

8310-21HD-0911



### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
  - The product must be properly installed, maintained and operated under normal conditions.
  - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
  - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



kuryakyn.com

**STEP 3** Determine the correct gasket for your application. Install **ONLY** the gasket that is called for in your application. Do not try to double up the gaskets.

**CAUTION! IMPORTANT** You must use the correct gasket for your year motorcycle! Using the incorrect gasket will cause damage to your paint job! Models thru 1995 use the beveled gasket, 1996 and newer use the OEM style split gasket. PIC 1 and PIC 2

**STEP 4** See PIC 3. Remove two of the small flat head screws from around the outer flange of the gas cap, 180° apart. In their place install the two brass studs. Screw the cap in as far as you can by hand. Carefully lay a screwdriver blade across these studs as shown and finish tightening. The caps should be good and snug, but don't over do it or you may score the paint around the cap.

**STEP 5** Remove the brass installation studs and replace the small flat head screws. Tighten securely. Test drive the bike and inspect for leaks. If a leak is detected, double check that the correct gasket has been installed and reassemble.

**STEP 6** Place the key on your key ring as it will be needed to open your cap!

**CAUTION!** Be sure the gas caps are sufficiently tight before riding.

**ATTENTION!** It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Küryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

