



MOTORCYCLE LIGHTING

www.namzccp.com

NAMZ Custom Cycle Products, Inc

1440 Ulmer Avenue
Oreland, PA 19075

Technical Support is available Monday-Friday, 9am-5pm EST via email at tech@namzccp.com or call us at 1-877-277-NAMZ.

Part Number: LLC-STTL-RS, LLC-STTL-SS & LLC-STTL-CS



(LLC-STTL-RS pictured)

Fitment: LLC-STTL-RS, LLC-STTL-SS & LLC-STTL-CS - Softail Replacement LED Taillight, RED, SMOKE or CLEAR LENS Fits: '06-later FXST, FXSTB, FXSTC, FXSTS and FLSTSB models. (with optional/integrated turn signals)

This product is intended: If you want to add some attention to your 2006 and later Softail's rear end, this is the taillight for you! An exact fit, replacement ultra-bright LED with optional color lenses and turn signals. Brighter than a factory taillight and the additional integrated turn signals allow for countless customization options. Easy to install, comes with OEM connector and license plate mount/reflector.

What is included in this kit?

- (1) Replacement LED Taillight with license plate bracket
- Installation instructions

Recommended Tools:

- #2 Phillips Screwdriver
- *Socket Set (if adding turn signal functions)
- *Heat Gun and Solder and Soldering Iron.

WARNING!

This product should be installed by a professional motorcycle technician or reputable shop/ dealership.

Improper installation may result in loss of taillight and/or turn signal functions.

1. Be sure the ignition switch is in the OFF position!
2. Start by placing our LED light housing into the new bracket. *(Be sure to route the wiring through the left side hole in the bracket.)*
3. Once in position, use the supplied screws to tighten the LED light onto the bracket. *(Do not use thread-lock or over tighten!)*
4. Find the reflector mount and place on top of license-plate bracket and bolt to light bracket assembly using the included hardware using a small amount of **blue** thread-lock.
5. Now disconnect the black, 4-position connector attached to the OEM taillight.
6. Remove the (4) bolts that hold the OEM license plate bracket assembly in place. *(We recommend to consult your service manual for in depth instructions)*
7. Once OEM taillight/license plate assembly has been removed, simply install the new LED light/frame assembly by plugging in the new connector and using a small amount of **blue** thread-lock on the mounting bolts.
8. Turn on the ignition and test for run and brake light functionality.

NOTE: The optional built-in turn signals will require left & right turn signal feeds from the OEM wiring. We recommend to solder or use NAMZ Lighting Splices for an easy install.



www.facebook.com/letriclightingco/



www.instagram.com/letriclightingco/



www.youtube.com/NAMZ-Custom-Cycle-Products