



Installation Instructions: Power Tune Duals

DISCLAIMER:

Qualified Manufacturer Declared Emissions Compliant Part for 2009 Harley-Davidson 49-State Non-CVO FL Touring Models Only

This header pipe is also applicable to 2009-2016 Harley-Davidson models when purchased as a component included with an S&S compliant exhaust system package with mufflers

SAFE INSTALLATION AND OPERATION RULES:

Before installing your new S&S part it is your responsibility to read and follow the installation and maintenance procedures in these instructions and follow the basic rules below for your personal safety.

- Gasoline is extremely flammable and explosive under certain conditions and toxic when breathed. Do not smoke. Perform installation in a well ventilated area away from open flames or sparks.
- If motorcycle has been running, wait until engine and exhaust pipes have cooled down to avoid getting burned before performing any installation steps.
- Before performing any installation steps disconnect battery to eliminate potential sparks and inadvertent engagement of starter while working on electrical components.
- Read instructions thoroughly and carefully so all procedures are completely understood before performing any installation steps. Contact S&S with any questions you may have if any steps are unclear or any abnormalities occur during installation or operation of motorcycle with a S&S part on it.
- Consult an appropriate service manual for your motorcycle for correct disassembly and reassembly procedures for any parts that need to be removed to facilitate installation.
- Use good judgment when performing installation and operating motorcycle. Good judgment begins with a clear head. Don't let alcohol, drugs, or fatigue impair your judgment. Start installation when you are fresh.
- Be sure all federal, state, and local laws are obeyed with the installation.
- For optimum performance and safety and to minimize potential damage to carb or other components, use all mounting hardware that is provided and follow all installation instructions.
- Motorcycle exhaust fumes are toxic and poisonous and must not be breathed. Run motorcycle in a well ventilated area where fumes can dissipate.

IMPORTANT NOTICE:

Statements in this instruction sheet preceded by the following words are of special significance.



WARNING

Means there is the possibility of injury to yourself or others.



CAUTION

Means there is the possibility of damage to the part or motorcycle.

NOTE

Other information of particular importance has been placed in italic type.

S&S recommends you take special notice of these items.

WARRANTY:

All S&S parts are guaranteed to the original purchaser to be free of manufacturing defects in materials and workmanship for a period of twelve (12) months from the date of purchase. Merchandise that fails to conform to these conditions will be repaired or replaced at S&S' option if the parts are returned to us by the purchaser within the 12 month warranty period or within 10 days thereafter.

In the event warranty service is required, the original purchaser must call or write S&S immediately with the problem. Some problems can be rectified by a telephone call and need no further course of action.

A part that is suspect of being defective must not be replaced by a Dealer without prior authorization from S&S. If it is deemed necessary for S&S to make an evaluation to determine whether the part was defective, a return authorization number must be obtained from S&S. The parts must be packaged properly so as to not cause further damage and be returned prepaid to S&S with a copy of the original invoice of purchase and a detailed letter outlining the nature of the problem, how the part was used and the circumstances at the time of failure. If after an evaluation has been made by S&S and the part was found to be defective, repair, replacement, or refund will be granted.

ADDITIONAL WARRANTY PROVISIONS:

- (1) S&S shall have no obligation in the event an S&S part is modified by any other person or organization.
- (2) S&S shall have no obligation if an S&S part becomes defective in whole or in part as a result of improper installation, improper maintenance, improper use, abnormal operation, or any other misuse or mistreatment of the S&S part.
- (3) S&S shall not be liable for any consequential or incidental damages resulting from the failure of an S&S part, the breach of any warranties, the failure to deliver, delay in delivery, delivery in non-conforming condition, or for any other breach of contract or duty between S&S and a customer.

ATTENTION INSTALLER (if other than owner):

Please forward this instruction sheet to the purchaser of this product. These instructions also contain valuable information necessary to the end user.

NOTES:

- 2009 models will require an oxygen sensor extension harness for the front head pipe. These extension harnesses are available through aftermarket dealers.
- This system may not be compatible with swing arm pivot suspension stabilizers.
- Right side floorboard must be mounted in the lowest position.
- When installing compliant S&S exhaust system on 2010 Street Glide®/ Road Glide® Custom models with OEM 2-1 exhaust system will require the purchase of the following Harley-Davidson® components: 65296-95A (hanger bracket), 65724-85 (rubber isolator), 65723-85 (exhaust clamp)



Ground and cornering clearance may be reduced. Clearance will be reduced when bikes are fitted with shorter shocks.

Tools Needed:

¼" drive ratchet	10mm Allen wrench
¼" drive ½" socket	⅝" nut driver or flat screwdriver
¼" drive ⅞" socket	⅞" box wrench
¼" drive 6" extension	½" box wrench
⅜" Allen wrench	⅝" box wrench
¼" Allen wrench	14mm box wrench
⅝" Allen wrench	15mm box wrench
6mm Allen wrench	22mm box wrench

PROCEDURE


The following installation procedure assumes that a stock exhaust system is being removed. If the bike you are working on has something other than the factory exhaust system, you may need to source some of the fasteners listed below.

1. Remove saddlebags.
2. Remove mufflers.
3. Remove right front floorboard and mounting brackets.
4. Remove heats shields and disconnect the oxygen sensors.
5. Remove the factory crossover pipe clamp and bracket from the back of transmission. Only the ¼" socket head screws will be re-used. The other parts are no longer needed.
6. Remove the exhaust port flange nuts, carriage bolt and lock nut that secure the header to the factory transmission side bracket. Remove the exhaust header. Save the ⅝-24 hex flange port nuts and ⅜" lock nut.
7. Remove and save oxygen sensors, retaining rings and exhaust flanges from old exhaust header.
8. Remove and discard exhaust port gaskets. Install new conical gaskets supplied in the kit.



New conical port gaskets (H-D 65324-83B) (S&S 106-5029) must be used to avoid leaks.

9. Install flanges and retaining rings on new exhaust header. Oxygen sensors and supplied adaptors should be installed at this time. Install P clamp on front header pipe in front of the collector but behind O2 sensor bung. See drawing for orientation. Use anti-seize on all threads.
10. Apply anti-seize to exhaust studs, and loosely Install the new header using saved ⅝-24 hex flange nuts. Seat rear pipe first then the front. Exert a firm pull forward on the front pipe, while keeping the rear pipe seated. Be careful not to damage gaskets. Do not fully tighten the flange nuts yet.
11. Use the provided ⅜" carriage bolt and flanged nut to secure the header P-clamp to the transmission side bracket. The P-clamp should be installed below the bracket. Do not fully tighten yet.
12. Locate the crossover pipe, and install the P-clamp and ⅝" carriage bolt as shown in **Picture 1**. Do not tighten this bolt yet, to allow left-right adjustment of the P-clamp.
13. Install the supplied Torca/AccuSeal pipe clamp on the expanded end of the crossover pipe with the bolt facing forward and the nut facing down (cannot be installed later). Applying anti seize to the threads and under the nut.



Picture 1

14. Position the crossover pipe under the oil pan and slide its expanded end onto the end of the front header pipe. Do not fully tighten the Torca/Accuseal pipe clamp at this time.
15. Locate the ¼" socket head cap screws from Step 5, apply Loctite, and secure the crossover P-clamp to the back of the transmission. Torque screws to 84-132 in*lbs.
16. Locate the ⅝" bolts and muffler clamps from Step 2, apply Loctite to the bolts and anti seize to the threads of the muffler clamps and install the mufflers. Muffler rear brackets should align side to side and up and down with the saddle bag support rear mounting brackets without stress, adjustment of the crossover pipe slip joint may be necessary. Do not fully tighten the ⅝" bracket bolts at this time.
17. Torque the port flange nuts evenly to 100-120 in*lbs. To ensure there are no leaks and the system is properly aligned the front and rear port nuts must be evenly torqued.

- Tighten the Torca/AccuSeal pipe clamp on the crossover pipe. For proper seal, the clamp should slightly (~1/16") overhang the end of the expanded crossover pipe. Make sure the clamp does not contact the frame.
- Tighten the flanged nut and carriage bolt used on the transmission side P-clamp to 20-25 ft*lbs, and tighten the 3/8" bolt and flanged nut on the crossover pipe P-clamp to 18 ft-lb.
- Clean header pipes and crossover (see step 26).
- Insert worm gear clamps into slots on the back side of the heat shields. All clamp screws except the upper two on the rear shield should be positioned so the screw heads can be accessed from the front or bottom of the headers. Tip: Insert clamps halfway into the slots and bend the ends outward to ease installation over header pipes.
- Install heat shields. Connect and loosely tighten all worm gear clamps. Position screw heads for easiest access and tighten with a 5/16" nut driver or screwdriver.
- Reinstall front floorboard in lowest position.
- Align and tighten the muffler clamps.
- Reconnect oxygen sensor electrical plugs.
- Before operating motorcycle, clean pipes and mufflers with soap and water or window cleaner. Any grease or oil will permanently burn onto pipes. Dry thoroughly
- Check all mounting hardware to be sure it is tight before and after first operation of motorcycle. Periodically, check tightness of all mounting hardware.

USE AND CARE:

- Wash your accessories with the same care you use when washing your motorcycle. Use mild soap and water. DO NOT use abrasive chemicals or cleaners, or high pressure washers.
- Cover ends of mufflers when washing motorcycle. Mufflers may internally corrode if saturated with water and allowed to sit.

Power Tune Dual Header Replacement Parts

1. Pipe, header, power tune dual, header pipe weldment,	551-0084
2. Gasket, exhaust, tapered, stainless steel, (2 Req)	106-5029
3. Adapter, oxygen sensor, 12mm to 18mm, stainless steel (2 Req).....	550-0375
4. Bolt, carriage, 3/8"-16 x 1-1/4"	500-0553
5. Nut, flanged, serrated, 3/8"-16	500-0554
6. Clamp, muffler, band style.....	551-0028
7. Tube, crossover, power tune dual, formed,	551-0080
8. Shield, left, power tune dual, chrome	551-0115
black.....	551-0116
9. Nut, HSFH, 5/16-18 UNC-2b x .283", Zinc, steel.....	50-5053-s
10. Clamp, p-style, crossover, power tune dual header,	551-0121
11. Bolt, carriage, 5/16"-18 x 3/4"	500-0555
12. Clamp, hose (8 Req).....	551-0124
13. Shield, front, power tune dual, Chrome	551-0097
Black.....	551-0098
14. Shield, rear, power tune dual, Chrome	551-0103
Black.....	551-0104
15. clamp, p-style, power tune dual, side.....	551-0119
Not Shown	
16. Hardware kit, power tune dual, header Includes items 2, 3, 4, 6, 7, 10, 11, 12, 13, and 16.....	551-0155

